



ZPMV2.E173761 Wiring, Printed - Component

Enhanced searching capability for this category can be found in UL's iQ Family of Databases (iq.ul.com).

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

RAYBEN PCB LTD

E173761

FLAT 6, 8TH FL

WINFUL CENTRE, 30 SHING YIP ST

KWUN TONG


KOWLOON, HONG KONG

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max	Solder		Max	Flame	Meets UL796 DSR	C T I
	Min	Edge			Area	Limits	Oper				
	mm(in)	mm(in)			Diam mm(in)	C	Temp C	Class			
Multilayer printed wiring boards.											
RB-06	0.04 (0.002)	0.12 (0.005)	17 (0.67) Int: 68	DS	25.4 (1.0)	288	20	130	V-0	All	-
RB-07	0.075 (0.003)	0.15 (0.006)	12 (0.47) Int: 68	DS	50.8 (2.0)	288	10	130	V-0	All	-
RB-08	0.15 (0.006)	0.225 (0.009)	34 (1.34) Int: 68	DS	25.4 (1.0)	288	10	130	V-0	All	-
RB-09	0.20 (0.008)	0.225 (0.009)	34 (1.34) Int: 102	DS	25.4 (1.0)	288	10	130	V-0	All	-
RB-12*	0.32 (0.013)	0.32 (0.013)	17 (0.67) Int: 204	DS	50.8 (2.0)	288	10	130	V-0	All	-
Single layer Metal Base printed wiring boards.											
RB-ALO1	0.16 (0.006)	0.25 (0.010)	34 (1.34)	SS	50.8 (2.0)	288	20	130	V-0	All	-
RB-ALO2	0.16 (0.006)	0.25 (0.010)	34 (1.34)	SS	50.8 (2.0)	288	20	130	V-0	All	-
RB-ALO3	0.15 (0.006)	0.20 (0.008)	34 (1.34)	SS	50.8 (2.0)	288	20	110	V-0	All	0
RB-ALO4	0.16 (0.006)	0.25 (0.010)	34 (1.34)	SS	50.8 (2.0)	288	10	90	V-0	All	-
RB-ALO5	0.16 (0.006)	0.25 (0.010)	34 (1.34)	SS	50.8 (2.0)	288	10	90	V-0	All	-
RB-ALO6	0.15 (0.006)	0.20 (0.008)	34 (1.34)	SS	50.8 (2.0)	288	20	90	V-0	All	0
Single layer printed wiring boards.											
RB-02	0.13 (0.005)	0.38 (0.015)	17 (0.67)	DS	25.4 (1.0)	260	12	130	V-0	All	-
RB-03	0.31 (0.012)	0.56 (0.022)	34 (1.34)	DS	25.4 (1.0)	260	15	105	V-0	All	-

RB-04	0.05 (0.002)	0.15 (0.006)	17 (0.67)	DS	25.4 (1.0)	288	20	130	V-0	All	-
RB-05	0.04 (0.002)	0.12 (0.005)	17 (0.67)	DS	50.8 (2.0)	288	20	130	V-0	All	-
RB-10	0.075 (0.003)	0.225 (0.009)	12 (0.47)	DS	25.4 (1.0)	288	10	130	V-0	All	-
RB-11	0.10 (0.004)	0.31 (0.012)	12 (0.47)	DS	50.8 (2.0)	288	10	130	V-0	All	-

* - External Cu thickness within 102 mic, Min width = 0.075, Min Edge width = 0.15 mm; External Cu thickness beyond 102 mic, Min/Edge width = 0.32 mm



Marking: Company name or trademark  or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2011-09-16

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright ?2011 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.





ZPMV8.E173761

Wiring, Printed Certified for Canada - Component

Enhanced searching capability for this category can be found in UL's iQ Family of Databases (iq.ul.com).

[Page Bottom](#)

Wiring, Printed Certified for Canada - Component

[See General Information for Wiring, Printed Certified for Canada - Component](#)

RAYBEN PCB LTD

E173761

FLAT 6, 8TH FL

WINFUL CENTRE, 30 SHING YIP ST



KWUN TONG

KOWLOON, HONG KONG

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max	Solder		Max	Flame Class	Meets UL796 DSR	C I
	Min	Edge			Area	Limits	Oper				
	mm(in)	mm(in)			Diam mm(in)	C	sec	C			
Multilayer printed wiring boards.											
RB-06	0.04 (0.002)	0.12 (0.005)	17 (0.67) Int: 68	DS	25.4 (1.0)	288	20	130	V-0	All	-
RB-07	0.075 (0.003)	0.15 (0.006)	12 (0.47) Int: 68	DS	50.8 (2.0)	288	10	130	V-0	All	-
RB-08	0.15 (0.006)	0.225 (0.009)	34 (1.34) Int: 68	DS	25.4 (1.0)	288	10	130	V-0	All	-
RB-09	0.20 (0.008)	0.225 (0.009)	34 (1.34) Int: 102	DS	25.4 (1.0)	288	10	130	V-0	All	-
RB-12*	0.32 (0.013)	0.32 (0.013)	17 (0.67) Int: 204	DS	50.8 (2.0)	288	10	130	V-0	All	-
Single layer Metal Base printed wiring boards.											
RB-ALO1	0.16 (0.006)	0.25 (0.010)	34 (1.34)	SS	50.8 (2.0)	288	20	130	V-0	All	-
RB-ALO2	0.16 (0.006)	0.25 (0.010)	34 (1.34)	SS	50.8 (2.0)	288	20	130	V-0	All	-
RB-ALO3	0.15 (0.006)	0.20 (0.008)	34 (1.34)	SS	50.8 (2.0)	288	20	110	V-0	All	0
RB-ALO6	0.15 (0.006)	0.20 (0.008)	34 (1.34)	SS	50.8 (2.0)	288	20	90	V-0	All	0
Single layer printed wiring boards.											
RB-02	0.13 (0.005)	0.38 (0.015)	17 (0.67)	DS	25.4 (1.0)	260	12	130	V-0	All	-
RB-03	0.31 (0.012)	0.56 (0.022)	34 (1.34)	DS	25.4 (1.0)	260	15	105	V-0	All	-
RB-04	0.05 (0.002)	0.15 (0.006)	17 (0.67)	DS	25.4 (1.0)	288	20	130	V-0	All	-
RB-05	0.04 (0.002)	0.12 (0.005)	17 (0.67)	DS	50.8 (2.0)	288	20	130	V-0	All	-

RB-10	0.075 (0.003)	0.225 (0.009)	12 (0.47)	DS	25.4 (1.0)	288	10	130	V-0	All	-
RB-11	0.10 (0.004)	0.31 (0.012)	12 (0.47)	DS	50.8 (2.0)	288	10	130	V-0	All	-

* - External Cu thickness within 102 mic, Min width = 0.075, Min Edge width = 0.15 mm; External Cu thickness beyond 102 mic, Min/Edge width = 0.32 mm

Marking: Company name or trademark  , or file number and type designation and Recognized Component Mark for Canada,  . May be followed by a suffix to denote factory identification or burning test classification.
Last Updated on 2011-09-16

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright ?2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

